AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method of storing an array of digital data into a memory, the

memory having a plurality of memory pages, at least one memory page which is addressed by a

row address having a first memory section and a second memory section, the method comprising

the steps of:

dividing the array of digital data into a plurality of block units, each of the block units

having a plurality of odd rows and a plurality of even rows, each of the odd rows and the even

rows having at least one byte; and

storing subsequent odd rows of at least one of the block units into consecutive storage

locations in the first memory section, and storing subsequent even rows of at least one of the

block units into consecutive storage locations in the second memory section.

2. (Original) The method of claim 1, wherein the array of digital data comprises a

picture in a video bit stream.

3. (Original) The method of claim 1, wherein the first memory section has a first number

of first areas and the second memory section has a second number of second areas, each of the

first areas and the second areas has consecutive storage locations, each of the first number and

the second number is equal to or larger than one.

4. (Original) The method of claim 3, wherein the first number is equal to the second

number.

Claim 5 (Cancelled)

6. (Original) The method of claim 3, wherein both the first number and the second

number have a value of one.

2 KM/RFG/cdr

Amendment dated February 20, 2007

Reply to Office Action of October 20, 2006

7. (Original) The method of claim 3, wherein both the first number and the second

number have a value of two.

8. (Original) The method of claim 1, wherein each of the block units has m rows,

wherein m is an integer equal to or larger than four.

9. (Original) The method of claim 8, wherein m is equal to thirty-two.

10. (Currently Amended) A method of storing an array of digital video data representing

a picture in a video bit stream into a memory, the memory having a plurality of memory pages,

each-at least one memory page which is addressed by a row address having a first memory

section and a second memory section, the method comprising the steps of:

dividing the array of digital video data into a plurality of block units, each of the block

units having a plurality of odd rows and a plurality of even rows, each of the odd rows and the

even rows having at least one byte; and

storing subsequent odd rows of at least one of the block units into consecutive storage

locations in the first memory section, and storing subsequent even rows of at least one of the

block units into consecutive storage locations in the second memory section.

11. (Original) The method of claim 10, wherein the first memory section has a first

number of first areas and the second memory section has a second number of second areas, each

of the first areas and the second areas has consecutive storage locations, each of the first number

and the second number is equal to or larger than one.

12. (Original) The method of claim 10, wherein each of the block units has m rows,

wherein m is an integer equal to or larger than four.

13. (Currently Amended) A method for storing an array of digital data representing a

picture into a memory and retrieving a prediction block of the picture from the memory, the

3 KM/RFG/cdr

Reply to Office Action of October 20, 2006

memory having a plurality of memory pages, each at least one memory page which is addressed

by a row address having a first memory section and a second memory section, the method

comprising the steps of:

dividing the array of digital video data into a plurality of block units, each of the block

units having a plurality of odd rows and a plurality of even rows, each of the odd rows and the

even rows having at least one byte;

storing subsequent odd rows of at least one of the block units into consecutive storage

locations in the first memory section, and storing subsequent even rows of at least one of the

block units into consecutive storage locations in the second memory section; and

retrieving the digital data representing the prediction block stored in the first memory

section, and retrieving the digital data representing the prediction block stored in the second

memory section.

14. (Original) The method of claim 13, wherein the first memory section has a first

number of first areas and the second memory section has a second number of second areas, each

of the first areas and the second areas has consecutive storage locations, each of the first number

4

and the second number is equal to or larger than one.

15. (Original) The method of claim 13, wherein each of the block units has m rows,

wherein m is an integer equal to or larger than four.

KM/RFG/cdr